



Building a Sustainable Tomorrow

Airfield Concrete Pavement Maintenance and Rehabilitation Strategies

September 19, 2016

CAPTG Workshop, Minneapolis

Rico Fung, P.Eng., Cement Association of Canada

Gary Mitchell, P.E., American Concrete Pavement Assoc.




Cement
Association
of Canada

Association
Canadienne
du Ciment





3 Types of Rehabilitation





Pavement Maintenance Logic


- Correct Repair Procedures
 - Minimize **FOD**
- Airfield Rigid Pavement Distress Identification
 - Load Related vs. Environmental or Materials Related





JP002P, May 2003

www.acpa.org





Performance Issues

- Airfield Functional Condition
 - FOD potential
 - Friction/Hydroplaning
- Airfield Distress
 - cracking (**saw & sealing**)
 - corner breaks, shattered panels (**full depth**)
 - spalling (**partial depth**)
 - roughness / polished (**grinding**)





Distress Classification

Cracking

- Extends through the depth of a slab
- Caused by:
 - Poor Design - Long joint spacing
 - Poor Construction (Over Finished Surfaces)
 - Curling / warping (Stabilized bases)
 - Dowel Restraint
 - Load





Cracks and Causes

- Full Width of Panel (Slab)
 - Environmental Distress
 - Sealing (Sawing) Most Effective
- Corner Cracks (Diagonal) -
 - Load Distress
 - Full Depth Replacement Mandatory
- Shattered Slabs - More than Four Pieces
 - Full Depth Replacement Required





Building a Sustainable Tomorrow

Rules of Thumb for Concrete Cracks (Environmental)

- to 1/4" (6mm) Leave alone
- 1/4" to 1/2" (6 to 12.5mm) Saw and Seal
- 3/8" to 3/4" (9.5 to 19mm, Spalled) Partial Depth Repair
- 3/4" to 1-1/2" (19 to 38mm) Saw and Seal
- 3/4 to 1-1/2 (19 to 38mm, Spalled) Full Depth Patching
- More than 1-1/2" (38mm) Full Depth Patching





Building a Sustainable Tomorrow

Concrete Slab Repair





Depth of Repairs

- Partial Depth - Intent is to bond repair material to existing concrete and be compatible in characteristics
- Full Depth - Intent is to make the repair a functional part of the existing slab.



Building a Sustainable Tomorrow

Distress Classification-Spalling

- Breaking, cracking, or chipping at joints or cracks
 - Incompressible in Joint/Crack
 - Material Durability Problems
 - Poor Construction Techniques
- Full Depth Repair Required when unsound material deeper than $\frac{1}{3}$ thickness






Building a Sustainable Tomorrow

Partial Depth Repairs

- Generally spall repairs
- Repairs localized distress in the top 1/3 of the slab
- Generally located at joints, but can be placed anywhere surface defects occur






Building a Sustainable Tomorrow


Minor Sliver Spalling

→ | | ← Up to 6 mm (1/4")



Will not affect performance
of new sealant

Serious Compression Spalling



Will not provide reasonable
surfaces for sealing




Building a Sustainable Tomorrow

Partial Depth Repairs

Finding Unsound Concrete

Sounding the pavement:

- Hammer
- Steel rod
- Steel chain






Building a Sustainable Tomorrow




Partial Depth Repairs



Building a Sustainable Tomorrow

Defining Repair Boundaries





Partial Depth Repairs




Building a Sustainable Tomorrow

Placing Materials

- Applying **bonding** agent
 - Cement grout or Epoxy
 - Coat all surfaces (horizontal & vertical)
 - Do not allow bonding agent to set



Partial Depth Repairs




Building a Sustainable Tomorrow


Finishing

- Match surrounding elevation
- Work tool from center toward edges

← Finishing Direction



Finishing Direction →






Full Depth Repairs



Building a Sustainable Tomorrow

- Repairs distresses greater than $\frac{1}{3}$ the slab depth.
- Consists of removing and replacing at least a portion of the existing slab to the bottom of the concrete.




Full Depth Repairs




Building a Sustainable Tomorrow

- Minimum Repair 600 mm/2 feet
- Full Depth Cut at Joints
- Diamond-Blades
- Tie to Existing





Gang Drill



Building a Sustainable Tomorrow





Cleaning Holes (Air Blast)




Building a Sustainable Tomorrow





Building a Sustainable Tomorrow


Dowel Bar Placement for Full Depth Repairs






Building a Sustainable Tomorrow

1




Inject Grout
to Back of Hole

2



Twist one turn
while pushing
in dowel

3



Place grout
retention disk to
hold in grout



09/07/2016

Repair Materials



Building a Sustainable Tomorrow

Ideal Repair Materials

- Good workability
- Quick mixing time
- Fast setting time
- Rapid strength development
- Low shrinkage
- Strong bonding capability
- Durability
- Thermal compatibility with concrete



Repair Materials



Building a Sustainable Tomorrow

Cementitious Materials

- High early strength concrete
 - CSA A3001 Type HE cement
 - With or without admixture
 - Reach 20.7 MPa/3000 psi in 24 hours
 - Use cement grout/epoxy bonding agent






Cross-Stitching

- Grouting of tiebars in holes drilled across nonworking longitudinal cracks at an angle to the pavement surface
- Prevents horizontal and vertical crack movements





Building a Sustainable Tomorrow

Cross-Stitching Schematic




Fig. 8.5 on p. 8.14





Building a Sustainable Tomorrow

Cross-Stitching

Drilling of Holes





Building a Sustainable Tomorrow

Cross-Stitching Grout Insertion





Building a Sustainable Tomorrow

Cross-Stitching

Bar Insertion





Building a Sustainable Tomorrow

Cross-Stitching

Final Grouting





Building a Sustainable Tomorrow

Diamond Grinding

- Improves safety and roughness by:
 - Smoothing the ride
 - Reestablishing the friction properties
 - Correcting the cross-slope





Building a Sustainable Tomorrow





Concrete Overlays for Airfield Pavements – A Long-Life Rehabilitation Alternative



Gary L. Mitchell, P.E.
Vice President – Airports and Pavement Technology
American Concrete Pavement Association





Concrete Overlays

Budgets

Airport Sponsors are
asked to more with less



Time

Airport Sponsor needs

- proactive, sustainable pavement Maintenance
- Longer lasting rehabilitation strategies
- Reasonable cost

Concrete overlays represent such strategies





HISTORICAL REVIEW

- Began in late forties and early fifties
- First used on Airports and Secondary Roads
- In mid-seventies acceptance grew
- By late eighties this was normal practice
- Then in early nineties Ultra-Thin Whitetopping
- Today concrete overlays are often used strategy





Building a Sustainable Tomorrow

RUNWAY WHITETOPPING - IOWA

1971	Storm Lake -	5"	IDOT	1992	Spencer -	6"	FAA
1979	Centerville -	5"	IDOT	1993	Oelwein -	5"	IDOT
1982	Clarion -	5"	IDOT	1994	Spencer -	6"	FAA
1983	Waverly -	5"	IDOT	1994	Muscatine -	7"	FAA
1987	Corning -	5"	IDOT	1996	Hampton -	6"	IDOT
1988	Carroll -	5"	IDOT	1996	Clarinda -	5"	FAA
1991	Fort Madison -	5"	IDOT	1998	Oskaloosa -	6"	FAA
				2001	Jefferson -	5"	FAA
				2001	Greenfield -	5"	IDOT
				2001	Webster City-	6"	FAA





Building a Sustainable Tomorrow

Benefits of Concrete Overlays



- Cost-effective solution
- Quick and convenient
- Easy to repair
- Durable rehabilitation tool
- Sustainability
 - Albedo
 - Longevity, and
 - Surface profile stability






Building a Sustainable Tomorrow

THE ADVANTAGE OF CONCRETE APRONS & TAXIWAYS

-  Concrete is resistant to deformation, rutting, “birdbaths”, etc.
-  Concrete is not damaged by fuel spillage, oil drippings, or jet heat and blast.






3-Year old Reconstruction

3-Year old Asphalt overlay
Reflective cracks

Family of Concrete Overlays





Building a Sustainable Tomorrow

Existing Asphalt






Recent Overlay Projects

Building a Sustainable Tomorrow

Airport Name	Bid Date	Type	PCCP SY & Depth	Price per SY
Williamsburg Co (SC) - apron	June 2004	WT = Unbonded over asphalt	7000 (5-inch)	\$41.96 (Bid SY/CY)
Cobb County (GA) - runway	Apr 2008	WT	70,881 (7-inch)	\$29.39
Lancaster County (SC) - runway	Apr 2009	WT	66,870 (6.5-inch)	\$22.75
Charleston (SC) Executive - runway	June 2009	Unbonded over PCCP	59,700 (11-inch)	\$39.45
Berkeley County (SC) - runway	June 2010	WT	36,260 (9-inch)	\$32.90
Augusta (GA) Regional - runway	Sept 2010	WT	141,308 (14-inch)	\$37.84

Charleston Executive





350' Extension

Batch Plant On-Site

Crushing Operation – Base Material


WW II Era PCCP

RW Width reduced to 100'

Asphalt Sep Layer



Quotes from Open House

- A Concrete Overlay kept us “out of the subgrade” vs. reconstruction option.
 - A Concrete Overlay raised our pavement elevation out of the high water table
 - Inch per Inch concrete was less expensive than the asphalt leveling (separation) layer
 - Our original PCCP surface lasted 60+ years, no reason why this surface cannot last another 60 years!
- 

Williamsburg Co Apron Whitetopping

Asphalt PCI = 53/16

Project Details / 2004

Two Alternatives
Volatile Material Cost
Alternate Bids Accepted

Contractor	Alternative Bid Amount (\$)	
	Asphalt	Concrete
A	\$474,770	\$421,625
B	\$482,725	-
C	-	\$454,510
D	-	\$521,521

Cobb Co - McCollum Field



7-in Whitetopping

@ 29.39 / SY

Berkeley County Whitetopping

March, 2011



John F. Kennedy International Airport




THE PORT AUTHORITY
OF NEW YORK & NEW JERSEY




John F. Kennedy International Airport

Building a Sustainable Tomorrow



JFK Whitetopping

Final Project Design




120 Days - Paved over 12,000 feet



THE PORT AUTHORITY
OF NEW YORK & NEW JERSEY






Runway Cross Section



Building a Sustainable Tomorrow

Construction Progress- Slipform Paving





Questions & Comments





Building a Sustainable Tomorrow

THANK YOU!

gmitchell@acpa.org

